

Super Flex Pig

6" – 12" & 16"



Description

The Super Flex Pigs are solid-cast polyurethane pigs available in up to four durometers designed for 6" through 12" & 16" pipe with multiple configurations of 3C, 3D2C, 5D2C, brushes, magnets, and transmitters for varying pipeline applications and pigging needs. The Super Flex Pig is a one-piece body design with a hollow core. This allows the pig to have maximum flexibility for maneuvering through all pipeline bends and valves while maintaining a superior seal. The one-piece body design also requires no assembly and reduces the load for ease of use. The Super Flex Pig, having a hollow core, allows for the expansion of the pig while under pressure resulting in better sealing and scraping of the pipeline. The hollow core also makes it suitable for transmitters. The Super Flex Pig provides multiple sealing surfaces and is an

excellent choice for removing liquids from the line, especially in wet gas systems. It performs also performs well at removing, paraffin and other debris from product and crude oil systems. The 3 types of Super Flex pigs can be configured and customized depending on the job requirements.

Options

- Sizes 6" – 12" and 16"
- 3C , 2D3C , 3D2C , 5D2C
- Brush Assemblies – Carbon Steel, Stainless Steel , Pro Stran
- Magnets
- Transmitter Compatible
- Several Durometer Hardnesses